

534.723

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/044263 A1

(51) International Patent Classification⁷: **C23C 14/56**,
16/54

(SE). ROSELL, Torsten [SE/SE]; Näckgränd 4, S-582 43
Linköping (SE).

(21) International Application Number:
PCT/SE2003/001741

(74) Agent: AWAPATENT I LINKÖPING AB; Platensgatan
9C, S-582 20 Linköping (SE).

(22) International Filing Date:
11 November 2003 (11.11.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0203332-2 13 November 2002 (13.11.2002) SE

(71) Applicant (*for all designated States except US*): IMPACT
COATINGS AB [SE/SE]; Westmansgatan 29, S-582 16
Linköping (SE).


(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): LJUNGCRANTZ,
Henrik [SE/SE]; Kobergsgränd 4, S-587 21 Linköping

[Continued on next page]

(54) Title: DEVICE FOR CARRYING OUT A SURFACE TREATMENT OF SUBSTRATES UNDER VACUUM



(57) Abstract: The present invention relates to a device for carrying out a surface treatment of substrates under vacuum, which comprises a housing (1) comprising chambers (2-5) communicate with a vacuum source, at least one of which chambers serves as vacuum lock to the remaining chambers when surface treatment processes are in progress. The housing (1) is divided into an upper and a lower housing half (6, 7) of which at least one has symmetrically distributed recesses (8). Pivotaly mounted between the housing halves (6, 7) is a revolver (9), which comprises recesses (10) in which substrate to be treated is placed. The housing halves (6, 7) are designed to be in two positions, in the first of which they are separated from the revolver (9) and in the second of which they are in contact therewith. In the first position the revolver (9) is designed to be turned to predefined rotational positions at which recesses in the housing halves (6, 7) and the revolver (9) coincide in the chambers (2-5). In the first position the vacuum lock can be opened and evacuated without disturbing the vacuum in other parts of the housing (1).

WO 2004/044263 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.